






LINAX PLUS

Floor stripper









Ingredients:

LINAX plus contains: less than 5% non-ionic surfactants, 5-15% Phosphate, Phenoxyethanol. Other ingerdients: water soluble solvents, solving agents.

pH-value: approx. 10.

Performance:

Effortlessly removes old, heavily worn wax and polymer films. Extremely well suited to sensitive coverings such as linoleum and rubber. Can be mixed with water in any proportion. No unpleasant odour during and after application. Takes effect quickly, low foaming and high material compatibility. Virtually non-slip during stripping.

Application notes:

All kinds of floorings. Exception: unsealed wooden floors.

Usage:

Depending on the nature and thickness of the dirt and care products to be removed, apply to the floor neat or di-luted with water to as much as 1:10. Leave to take effect for 10 min. and work with a scrubber or floor machine. Pick up dissolved dirt and film residues. Wipe off when wet. It is advisable to work on small sections at a time.

Precautions for use:

During the application, ensure adequate ventilation of the room. Keep container tightly closed and out of the reach of children. Do not let loose dirt or film rests dry again.

Ecology:

This product is subject to regulations governing the environmental compatibility of washing and cleaning agents and the associated regulations on the biological degradability of the raw materials used.

Comprehensive information about the environmental characteristics of this product is available on request.

Give only comletely packaging to special waste disposer.

This product is designated for industrial use.

Product code: GG 20

UBA 0947 0638

Waste Key: 070608

| ArtNr.: 03724 | 200 l |
|---------------|-------|
| ArtNr.: 03685 | 10 |





