



FUNCTIONAL CHARACTERISTICS

Poly Description of this block and is joined to the foam using the INTEGRAL FORM system, without seams or stitching. A Description of this block and is joined to the foam using the INTEGRAL FORM system, without seams or stitching. A Description of the seat and the block and the specific prevent life from reaching the foam, delaying the spread of flames and emission of toxic gases. Solution backrest to prevent fire from reaching the foam, delaying the spread of flames and emission of toxic gases.

Adresa: ul.Braka Mingovi 18, 7000 Bitola; tel: 047/203-330 ,203 900ul.A.Guslarot.1a 02/329 8 130 Skopje www.electrolux.com.mk www.elektroluks.com.mk e-mail: elek-palenzo@mt.net.mk

sprofivno se snosat posledici vo smislana clenovite 163 i 164 od krivicniot zakon R.M. (povreda na avtorsko pravo)

critez e sopstvenost na Electrolux-Bitola. Bez negovo pismeno odobruvanje istiot nesmee da se prepisuva "umnozuva niti kopira" bez soglasnost od Elrctroluks



Backrest padding is anatomically contoured and incorporates grooves in a 'T' form. Seat padding is also anatomically contoured, with a completely smooth, groove-free surface to prevent accumulation of dirt. The back surfaces of the seat and backrest are protected by shells injected with IF727 material. These shells are fully washable and protect upholstery.











The seat folds automatically using a double-spring system contained within the shell (tested at 500,000 cycles). The system does not require lubrication or maintenance.

Each chair is mounted on a central pedestal. This pedestal is attached to an internal bridge that links the individual units to form rows that are completely rigid and stable. Pedestals are made of tubular steel finished in black epoxy paint. If necessary, the base of the pedestal can be adjusted to the slope of the hall where seating is installed.

Chair arms are made of polyurethane foam with an internal metal structure. Side frames are also finished in polyurethane, textured with circular forms.

Perforations on the shell of the seat improve acoustic absorption when chairs are unoccupied.

Adresa: ul.Braka Mingovi 18, 7000 Bitola; tel: 047/203-330 ,203 900ul.A.Guslarot.1a 02/329 8 130 Skopje www.electrolux.com.mk www.elektroluks.com.mk e-mail: elek-palenzo@mt.net.mk

criez e sopstvenost na Electrolux-Bitola. Bez negovo pismeno odobruvanje istiot nesmee da se prepisuva "umnozuva niti kopira bez soglasnost od Elrctroluks smislana clenovite 163 i 164 od krivicniot zakon R.M. (povreda na avtorsko pravo)




PLX – new anti-panic system for writing tablets. When chairs are vacated, writing tablets are automatically stored in the side frame. This clears the way for users in the event that the space needs to be evacuated in a stored in the side frame. This clears the way for users in the event that the space needs to be evacuated in Elektroluks is registered trademark of Elektrouks companies in Macedonia and an emergency. This folding movement is rapid and precise thanks to a new hinge system that facilitates synchronized turning on two axes. The system is maintenance-free.

86 23.2 55 37.4" 95 55 - 57 32 12.6" 21.6" - 22.2 37.4" 95

Ovoj crtez e sopstvenost na Electrolux-Bitola. Bez negovo pismeno odobruvanje istiot nesmee da se prepisuva "umnozuva niti kopira" bez soglasnost od Elrctroluks vo sprotivno se snosat posledici vo smislana clenovite 163 i 164 od krivicniot zakon R.M. (povreda na avtorsko pravo)

> Adresa: ul.Braka Mingovi 18, 7000 Bitola; tel: 047/203-330 ,203 900ul.A.Guslarot.1a 02/329 8 130 Skopje www.electrolux.com.mk www.elektroluks.com.mk e-mail: elek-palenzo@mt.net.mk





TECHNICAL CHARACTERISTICS

STRUCTURE:

Ovoi criez e sopstvenost na Electrolux-Bitola. Bez negovo pismeno odobruvanje istiot nesmee da se prepisuva "umnozuva niti kopira bez soglasnost od Elrctroluks

vo sprotivno se snosat posledici vo smislana clenovite 163 i 164 od krivicniot zakon R.M. (povreda na avtorsko pravo)

Steel tube and plate, arc welds with continuous wire feed

POLYURETHANE FOAM:

- Seat density: 65 kg/m³
- Backrest density: 57 kg/m³

PAINT:

- Electrostatic epoxy powder
- Coat thickness: 70-80 microns
- Grid adherence: 100%

UPHOLSTERY: Pilling: Index 5 BS 5811 Adresa: ul.Braka Mingovi 18, 7000 Bitola; tel: 047/203-330 ,203 900ul.A.Guslarot.1a 02/329 8 130 Skopje www.electrolux.com.mk www.elektroluks.com.mk e-mail: elek-palenzo@mt.net.mk

Elektroluks is registered trademark of Elektrouks companies in Macedonia and other countries



Electrolux

Factory - Intelligent Engeneering, Shop, Sales and Service

INJECTED SHELLS:

- Material: Polypropylene copolymer IF-727
- Tensile strength at break DIN 53455: 28 N/mm²
- Impact strength DIN 53453: No break

FIRE BEHAVIOUR STANDARDS:

- United Kingdom: BS 5852. Section 5. Ignition sources 0, 1 and 5
- Germany: DIN 54342, part 1 and 2
- Italy: CSE RF/4/83 class 1. IM
- Spain/France: UNE 2372/NF 92-503
- Upholstery: M1/Foam: M4/Plastic: M3
- USA: CAL TB 133 (with certified fabric)

WEIGHT: 29 kg

VOLUME: 0.19 m³ (per unit, disassembled)

Ovoj crtez e sopstvenost na Electrolux-Bitola. Bez negovo pismeno odobruvanje istiot nesmee da se prepisuva "umnozuva niti kopira" bez soglasnost od Elrctroluks vo sprotivno se snosat posledici vo smislana clenovite 163 i 164 od krivicniot zakon R.M. (povreda na avtorsko pravo) Elektroluks is registered trademark of Elektrouks companies in Macedonia and other countries